

INSTALLATION AND USE

Surface Preparation

Ensure that all supports are healthy and clean, free of irregularities. For wet rooms (shower, basin...), waterproof the surface before tiling.

Installation

To ensure that the mosaics are correctly laid, we recommend the use of white Flex Adhesive, a high-performance cement-based adhesive which is specially designed for laying terracotta mosaics, stone mosaics, glass mosaics and porcelain tiles. Use the smooth side of a notched trowel to spread the adhesive evenly over the wall and then "comb" it with the notched side (minimum notch size 3mm). To lay the mosaic sheets, press them down evenly with a rubber trowel and make sure that the distance between each sheet is the same as the joint between the mosaic chips to ensure a uniform appearance and joints of the same width

Grouting

We recommend the use of Colorstuk Rapid, a fast setting grouting mortar available in different colours, with an excellent mechanical resistance, low water absorption and anti-fungal qualities. Colors. Application: Spread the grouting material using a rubber trowel, filling in the joints completely. Use the same trowel to remove any excess material.

Cleaning

Before the grouting material sets, any remains must be removed with a sponge or cloth. The grouting material must not be allowed to dry too much before doing this or it will hinder the cleaning of the mosaics.

The use of detergents and abrasives such as cleaning powders may cause irreparable damage to the sections. Our mosaic are pre-sealed. After installation, we recommend to seal with Fila W68 or equivalent.



Professionnals:
bonjour@zelij.com

Private & general enquiries:
contact@zelij.com

+33 (0)562 481 809

[@ateliers.zelij](https://www.ateliers.zelij.com)

www.zelij.com

All right reserved © 2026

Ateliers Zelij | Créateurs de surfaces